



BILLING CODE: 3510 DS-P

DEPARTMENT OF COMMERCE

INTERNATIONAL TRADE ADMINISTRATION

(A-433-812, A-423-812, A-427-828, A-428-844, A-475-834, A-588-875, A-580-887, A-583-858)

Certain Carbon and Alloy Steel Cut-To-Length Plate from Austria, Belgium, France, the Federal Republic of Germany, Italy, Japan, the Republic of Korea, and Taiwan: Amended Final Affirmative Antidumping Determinations for France, the Federal Republic of Germany, the Republic of Korea and Taiwan, and Antidumping Duty Orders

AGENCY: Enforcement and Compliance, International Trade Administration, Department of Commerce

SUMMARY: Based on affirmative final determinations by the Department of Commerce (the Department) and the International Trade Commission (the ITC), the Department is issuing antidumping duty orders on certain carbon and alloy steel cut-to-length plate (CTL plate) from Austria, Belgium, France, the Federal Republic of Germany (Germany), Italy, Japan, the Republic of Korea (Korea), and Taiwan. In addition, the Department is amending its final affirmative determinations with respect to France, Germany, Korea, and Taiwan.

DATES: [Insert date of publication in the *Federal Register*].

FOR FURTHER INFORMATION CONTACT: Edythe Artman at (202) 482-3931

(Austria), Andrew Medley (202) 482-6345 (Belgium), Terre Keaton Stefanova at (202) 482-1280 (France), David Goldberger at (202) 482-4136 (Germany), Alice Maldonado at (202) 482-4682 (Italy), Kabir Archuletta at (202) 482-2593 (Japan), Michael J. Heaney at (202) 482-4475 (Korea), or Tyler Weinhold (Taiwan) at (202) 482-1121, AD/CVD Operations, Enforcement and Compliance, International Trade Administration, U.S. Department of Commerce, 1401 Constitution Avenue NW, Washington, DC 20230.

SUPPLEMENTARY INFORMATION:

Background

In accordance with sections 735(d) and 777(i)(1) of the Tariff Act of 1930, as amended (the Act), and 19 CFR 351.210(c), on April 4, 2017, the Department published its affirmative final determinations in the less-than-fair-value (LTFV) investigations of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan.¹ On May 18, 2017, the ITC notified the Department of its affirmative determination, pursuant to section 735(d) of the Act, that an industry in the United States is materially injured within the meaning of section 735(b)(1)(A)(i) of the Act, by reason of the LTFV imports of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan, and its determination that critical circumstances do not exist with respect to imports of subject merchandise from Austria, Belgium, and Italy that are subject to the Department's affirmative critical circumstances findings.²

¹ See *Certain Carbon and Alloy Steel Cut-To-Length Plate from Austria: Final Determination of Sales at Less Than Fair Value and Final Affirmative Determination of Critical Circumstances*, 82 FR 16366 (April 4, 2017); *Certain Carbon and Alloy Steel Cut-To-Length Plate from Belgium: Final Determination of Sales at Less Than Fair Value and Final Determination of Critical Circumstances, in Part*, 82 FR 16378 (April 4, 2017); *Certain Carbon and Alloy Steel Cut-to-Length Plate from France: Final Determination of Sales at Less Than Fair Value*, 82 FR 16363 (April 4, 2017) (*France Final*); *Certain Carbon and Alloy Steel Cut-to-Length Plate from the Federal Republic of Germany: Final Determination of Sales at Less Than Fair Value*, 82 FR 16360 (April 4, 2017) (*Germany Final*); *Certain Carbon and Alloy Steel Cut-to-Length Plate from Italy: Final Determination of Sales at Less Than Fair Value and Final Affirmative Determination of Critical Circumstances*, 82 FR 16345 (April 4, 2017); *Certain Carbon and Alloy Steel Cut-to-Length Plate from Japan: Final Determination of Sales at Less Than Fair Value*, 82 FR 16349 (April 4, 2017); *Certain Carbon and Alloy Steel Cut-To-Length Plate from the Republic of Korea: Final Determination of Sales at Less Than Fair Value and Final Negative Critical Circumstances Determination*, 82 FR 16369 (April 4, 2017) (*Korea Final*); and *Certain Carbon and Alloy Steel Cut-To-Length Plate from Taiwan: Final Determination of Sales at Less Than Fair Value and Final Negative Determination of Critical Circumstances Final*, 82 FR 16372 (April 4, 2017) (*Taiwan Final*).

² See Letter regarding CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan Australia, Brazil, China, Indonesia, and Portugal (May 18, 2017) (ITC Letter). See also *Carbon and Alloy Steel Cut-to-Length Plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan Investigation Nos. 701-TA-561 and 731-TA-1317-1318, 1321-1325, and 1327 (Final)* USITC Publication 4691 (May 2017) (ITC Report).

Scope of the Orders

The merchandise covered by these orders is certain CTL plate. *See* Appendix A for Austria, Belgium, France, Germany, and Italy, Appendix B for Korea, Appendix C for Japan, and Appendix D for Taiwan.

Amendment to Final Determinations

A ministerial error is defined as an error in addition, subtraction, or other arithmetic function, clerical error resulting from inaccurate copying, duplication, or the like, and any other similar type of unintentional error which the Secretary considers ministerial.³

France Amended Final Determination

Pursuant to section 735(e) of the Act and 19 CFR 351.224(e) and (f), the Department is amending the *France Final* to reflect the correction of ministerial errors in the final estimated weighted-average dumping margin calculated for Dillinger France S.A. (Dillinger France). In addition, because Dillinger France's estimated weighted-average dumping margin is the basis for the estimated weighted-average dumping margin determined for all other French producers and exporters of subject merchandise, we also are revising the "all-others" rate in *France Final*.^{4,5}

Germany Amended Final Determination

Pursuant to section 735(e) of the Act and 19 CFR 351.224(e) and (f), the Department is amending the *Germany Final* to reflect the correction of a ministerial error in the final estimated weighted-average dumping margin calculated for AG der Dillinger Hüttenwerke (Dillinger Germany). In addition, because the Department determined the estimated weighted-average

³ *See* section 735(e) of the Act and 19 CFR 351.224(f).

⁴ *See* "Estimated Weighted-Average Dumping Margins" section below.

⁵ *See* Memorandum, "Less-Than-Fair-Value Investigation of Certain Carbon and Alloy Steel Cut-To-Length Plate from France: Allegation of Ministerial Error in the Final Determination," dated April 28, 2017.

dumping margin for all other German producers and exporters of subject merchandise based on a weighted-average of the respondents' estimated weighted-average dumping margins using publicly-ranged quantities for their sales of subject merchandise, we also are revising the "all-others" rate in *Germany Final*.^{6,7}

Korea Amended Final Determination

Pursuant to section 735(e) of the Act and 19 CFR 351.224(e) and (f), the Department is amending the *Korea Final* to reflect the correction of ministerial errors in the final estimated weighted-average dumping margin calculated for POSCO. In addition, because POSCO's estimated weighted-average dumping margin is the basis for the estimated weighted-average dumping margin for all other Korean producers and exporters of subject merchandise, we also are revising the "all-others" rate in *Korea Final*.^{8,9}

Taiwan Amended Final Determination

Pursuant to section 735(e) of the Act and 19 CFR 351.224(e) and (f), the Department is amending the *Taiwan Final* to reflect the correction of a ministerial error in the final estimated weighted-average dumping margin calculated for China Steel Corporation. In addition, because the Department determined the estimated weighted-average dumping margin for all other Taiwanese producers and exporters of subject merchandise based on a simple average of the respondents' estimated weighted-average dumping margins, we also are revising the "all-others"

⁶ See the "Estimated Weighted-Average Dumping Margins" section below.

⁷ See Memorandum, "Less-Than-Fair-Value Investigation of Certain Carbon and Alloy Steel Cut-To-Length Plate from Germany: Allegation of Ministerial Error in the Final Determination," dated May 2, 2017.

⁸ See the "Estimated Weighted-Average Dumping Margins" section below.

⁹ See Memorandum, "Antidumping Duty Less-Than-Fair-Value Investigation of Certain Carbon and Alloy Steel Cut-To-Length Plate from the Republic of Korea: Allegation of Ministerial Error in the Final Determination," dated concurrently with this notice.

rate in *Taiwan Final*.^{10,11} In addition, in the *Taiwan Final*, we identified an error in the scope language for Taiwan included in the Appendix. See Appendix D, below, for the corrected scope language.

Antidumping Duty Orders

As stated above, on May 18, 2017, in accordance with sections 735(b)(1)(A)(i) and 735(d) of the Act, the ITC notified the Department of its determination that the industry in the United States producing CTL plate is materially injured with respect to CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan and its determination that critical circumstances do not exist with respect to imports of subject merchandise from Austria, Belgium, and Italy that are subject to the Department's affirmative critical circumstances finding.¹² Therefore, in accordance with section 735(c)(2) of the Act, we are issuing these antidumping duty orders. Because the ITC determined that imports of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan are materially injuring a U.S. industry, unliquidated entries of such merchandise from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan, entered or withdrawn from warehouse for consumption, are subject to the assessment of antidumping duties.

Therefore, in accordance with section 736(a)(1) of the Act, the Department will direct U.S. Customs and Border Protection (CBP) to assess, upon further instruction by the Department, antidumping duties equal to the amount by which the NV of the merchandise exceeds the export price (or constructed export price) of the merchandise, for all relevant entries

¹⁰ See the "Estimated Weighted-Average Dumping Margins" section below.

¹¹ See Memorandum, "Amended Final Determination of the Less-Than-Fair-Value Investigation of Carbon and Alloy Steel Cut-to-Length Plate from Taiwan: Allegation of Ministerial Error for China Steel Corporation," dated concurrently with this notice.

¹² See ITC Letter and ITC Report.

of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan. Antidumping duties will be assessed on unliquidated entries of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan entered, or withdrawn from warehouse, for consumption on or after November 14, 2016, the date of publication of the preliminary determinations,¹³ but will not include entries occurring after the expiration of the provisional measures period and before publication in the *Federal Register* of the ITC's injury determination as further described below.

Continuation of Suspension of Liquidation

In accordance with section 735(c)(1)(B) of the Act, we will instruct CBP to continue to suspend liquidation on all relevant entries of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan. These instructions suspending liquidation will remain in effect until further notice.

We will also instruct CBP to require cash deposits for estimated antidumping duties equal to the amounts as indicated below. Accordingly, effective on the date of publication in the *Federal Register* of the ITC's affirmative injury determinations, CBP will require, at the same

¹³ See *Certain Carbon and Alloy Steel Cut-To-Length Plate from Austria: Preliminary Determination of Sales at Less Than Fair Value and Postponement of the Final Determination*, 81 FR 79416 (November 14, 2016) (*Austria Prelim*); *Certain Carbon and Alloy Steel Cut-To- Length Plate from Belgium: Preliminary Determination of Sales at Less Than Fair Value and Postponement of Final Determination*, 81 FR 79431 (November 14, 2016) (*Belgium Prelim*); *Certain Carbon and Alloy Steel Cut-To-Length Plate from France: Preliminary Determination of Sales at Less Than Fair Value and Postponement of Final Determination*, 81 FR 79437 (November 14, 2016) (*France Prelim*); *Certain Carbon and Alloy Steel Cut-to-Length Plate from the Federal Republic of Germany: Preliminary Determination of Sales at Less Than Fair Value and Postponement of Final Determination*, 81 FR 79446 (November 14, 2016) (*Germany Prelim*); *Certain Carbon and Alloy Steel Cut-To-Length Plate from Italy: Preliminary Determination of Sales at Less Than Fair Value, Affirmative Determination of Critical Circumstances, and Postponement of Final Determination*, 81 FR 79423 (November 14, 2016) (*Italy Prelim*); *Certain Carbon and Alloy Steel Cut-To-Length Plate from Japan: Preliminary Determination of Sales at Less Than Fair Value and Postponement of Final Determination*, 81 FR 79427 (November 14, 2016) (*Japan Prelim*); *Certain Carbon and Alloy Steel Cut-to-Length Plate from the Republic of Korea: Affirmative Preliminary Determination of Sales at Less Than Fair Value and Postponement of Final Determination*, 81 FR 79441 (November 14, 2016) (*Korea Prelim*); and *Certain Carbon and Alloy Steel Cut-To-Length Plate from Taiwan: Preliminary Determination of Sales at Less Than Fair Value*, 81 FR 79420 (November 14, 2016) (*Taiwan Prelim*).

time as importers would normally deposit estimated duties on this subject merchandise, a cash deposit equal to the estimated weighted-average dumping margins listed below.¹⁴ The relevant “all-others” rates apply to all producers or exporters not specifically listed, as appropriate.

Provisional Measures

Section 733(d) of the Act states that instructions issued pursuant to an affirmative preliminary determination may not remain in effect for more than four months, except where exporters representing a significant proportion of exports of the subject merchandise request the Department to extend that four-month period to no more than six months. At the request of exporters that account for a significant proportion of exports of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan, we extended the four-month period to six months in each proceeding.¹⁵ In the underlying investigations, the Department published the preliminary determinations on November 14, 2016. Therefore, the extended period, beginning on the date of publication of the preliminary determinations, ended on May 12, 2017.

Therefore, in accordance with section 733(d) of the Act and our practice, we will instruct CBP to terminate the suspension of liquidation and to liquidate, without regard to antidumping duties, unliquidated entries of CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan entered, or withdrawn from warehouse, for consumption after May 12, 2017, the date on which the provisional measures expired, until and through the day preceding the date of publication of the ITC’s injury determinations in the *Federal Register*. Suspension of

¹⁴ See section 736(a)(3) of the Act.

¹⁵ See *Austria Prelim*, *Belgium Prelim*, *France Prelim*, *Germany Prelim*, *Italy Prelim*, *Japan Prelim*, *Korea Prelim*, and *Taiwan Prelim*.

liquidation will resume on the date of publication of the ITC's determination in the *Federal Register*.

Critical Circumstances

With regard to the ITC's negative critical circumstances determination on imports of CTL plate from Austria, Belgium, and Italy, we will instruct CBP to lift suspension and to refund any cash deposits made to secure the payment of estimated antidumping duties with respect to entries of subject merchandise entered, or withdrawn from warehouse, for consumption on or after August 16, 2016 (*i.e.*, 90 days prior to the date of publication of the *Austria Prelim*, *Belgium Prelim*, and *Italy Prelim*), but before November 14, 2016 (*i.e.*, the date of publication of the *Austria Prelim*, *Belgium Prelim*, and *Italy Prelim*).

Estimated Weighted-Average Dumping Margins

The estimated weighted-average dumping margins for each antidumping order are as follows:

Austria	Producer/Exporter	Estimated Weighted-Average Dumping Margin (percent)
	Bohler Bleche GmbH & Co KG, Bohler Edelstahl GmbH & Co KG, Bohler International GmbH, voestalpine Grobblech GmbH, and voestalpine Steel Service Center GmbH	53.72
	All Others	53.72

Belgium	Producer/Exporter	Estimated Weighted-Average Dumping Margins (percent)
	Industeel Belgium S.A.	5.40

	NLMK Clabecq S.A., NLMK Plate Sales S.A., NLMK Sales Europe S.A., NLMK Manage Steel Center S.A., and/or NLMK La Louviere S.A.	51.78
	All Others	5.40

France	Producer/Exporter	Estimated Weighted- Average Dumping Margin (percent)
	Dillinger France S.A	6.15
	Industeel France S.A.	148.02
	All Others	6.15

Germany	Producer/Exporter	Estimated Weighted- Average Dumping Margin (percent)
	AG der Dillinger Hüttenwerke	5.52
	Ilseburger Grobblech GmbH, Salzgitter Mannesmann Grobblech GmbH, Salzgitter Flachstahl GmbH, and Salzgitter Mannesmann International GmbH	22.90
	All Others	21.04

Italy	Producer/Exporter	Estimated Weighted-Average Dumping Margins (percent)
	NLMK Verona SpA	22.19
	Officine Tecnosider s.r.l.	6.08
	Marcegaglia SpA	22.19
	All Others	6.08

Japan	Producer/Exporter	Estimated Weighted-Average Dumping Margin (percent)
	Tokyo Steel Manufacturing Co., Ltd.	14.79
	JFE Steel Corporation	48.67
	Shimabun Corporation	48.67
	All Others	14.79

Korea	Producer/Exporter	Estimated Weighted-Average Dumping Margin (percent)
	POSCO	7.10
	All Others	7.10

Taiwan	Producer/Exporter	Estimated Weighted-Average Dumping Margin (percent)
	China Steel Corporation	75.42
	Shang Chen Steel Co., Ltd.	3.62
	All Others	39.52

Notifications to Interested Parties

This notice constitutes the antidumping duty orders with respect to CTL plate from Austria, Belgium, France, Germany, Italy, Japan, Korea, and Taiwan pursuant to section 736(a) of the Act. Interested parties can find a list of antidumping duty orders currently in effect at <http://enforcement.trade.gov/stats/iastats1.html>.

These amended final determinations and orders are published in accordance with sections 735(e) and 736(a) of the Act and 19 CFR 351.210(c), 351.211(b), and 351.224(e) and (f).

Ronald K. Lorentzen

Ronald K. Lorentzen
Acting Assistant Secretary
for Enforcement and Compliance

May 19, 2017

Date

APPENDICES

A) Scope of the Orders for CTL plate from Austria, Belgium, France, Germany, and Italy

The products covered by these orders are certain carbon and alloy steel hot-rolled or forged flat plate products not in coils, whether or not painted, varnished, or coated with plastics or other non-metallic substances (cut-to-length plate). Subject merchandise includes plate that is produced by being cut-to-length from coils or from other discrete length plate and plate that is rolled or forged into a discrete length. The products covered include (1) Universal mill plates (*i.e.*, flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1250 mm, and of a thickness of not less than 4 mm, which are not in coils and without patterns in relief), and (2) hot-rolled or forged flat steel products of a thickness of 4.75 mm or more and of a width which exceeds 150 mm and measures at least twice the thickness, and which are not in coils, whether or not with patterns in relief. The covered products described above may be rectangular, square, circular or other shapes and include products of either rectangular or non-rectangular cross-section where such non-rectangular cross-section is achieved subsequent to the rolling process, *i.e.*, products which have been “worked after rolling” (*e.g.*, products which have been beveled or rounded at the edges).

For purposes of the width and thickness requirements referenced above, the following rules apply:

- (1) except where otherwise stated where the nominal and actual thickness or width measurements vary, a product from a given subject country is within the scope if application of either the nominal or actual measurement would place it within the scope based on the definitions set forth above, and
- (2) where the width and thickness vary for a specific product (*e.g.*, the thickness of certain products with non-rectangular cross-section, the width of certain products with non-rectangular shape, *etc.*), the measurement at its greatest width or thickness applies.

Steel products included in the scope of this order are products in which: (1) iron predominates, by weight, over each of the other contained elements; and (2) the carbon content is 2 percent or less by weight.

Subject merchandise includes cut-to-length plate that has been further processed in the subject country or a third country, including but not limited to pickling, oiling, levelling, annealing, tempering, temper rolling, skin passing, painting, varnishing, trimming, cutting, punching, beveling, and/or slitting, or any other

processing that would not otherwise remove the merchandise from the scope of the order if performed in the country of manufacture of the cut-to-length plate.

All products that meet the written physical description, are within the scope of this order unless specifically excluded or covered by the scope of an existing order. The following products are outside of, and/or specifically excluded from, the scope of this order:

- (1) products clad, plated, or coated with metal, whether or not painted, varnished or coated with plastic or other non-metallic substances;
- (2) military grade armor plate certified to one of the following specifications or to a specification that references and incorporates one of the following specifications:
 - MIL-A-12560,
 - MIL-DTL-12560H,
 - MIL-DTL-12560J,
 - MIL-DTL-12560K,
 - MIL-DTL-32332,
 - MIL-A-46100D,
 - MIL-DTL-46100-E,
 - MIL-46177C,
 - MIL-S-16216K Grade HY80,
 - MIL-S-16216K Grade HY100,
 - MIL-S-24645A HSLA-80;
 - MIL-S-24645A HSLA-100,
 - T9074-BD-GIB-010/0300 Grade HY80,
 - T9074-BD-GIB-010/0300 Grade HY100,
 - T9074-BD-GIB-010/0300 Grade HSLA80,
 - T9074-BD-GIB-010/0300 Grade HSLA100, and
 - T9074-BD-GIB-010/0300 Mod. Grade HSLA115,

except that any cut-to-length plate certified to one of the above specifications, or to a military grade armor specification that references and incorporates one of the above specifications, will not be excluded from the scope if it is also dual- or multiple-certified to any other non-armor specification that otherwise would fall within the scope of this order;

- (3) stainless steel plate, containing 10.5 percent or more of chromium by weight and not more than 1.2 percent of carbon by weight;
- (4) CTL plate meeting the requirements of ASTM A-829, Grade E 4340 that are over 305 mm in actual thickness;

- (5) Alloy forged and rolled CTL plate greater than or equal to 152.4 mm in actual thickness meeting each of the following requirements:
- (a) Electric furnace melted, ladle refined & vacuum degassed and having a chemical composition (expressed in weight percentages):
- Carbon 0.23-0.28,
 - Silicon 0.05-0.20,
 - Manganese 1.20-1.60,
 - Nickel not greater than 1.0,
 - Sulfur not greater than 0.007,
 - Phosphorus not greater than 0.020,
 - Chromium 1.0-2.5,
 - Molybdenum 0.35-0.80,
 - Boron 0.002-0.004,
 - Oxygen not greater than 20 ppm,
 - Hydrogen not greater than 2 ppm, and
 - Nitrogen not greater than 60 ppm;
- (b) With a Brinell hardness measured in all parts of the product including mid thickness falling within one of the following ranges:
- (i) 270-300 HBW,
 - (ii) 290-320 HBW, or
 - (iii) 320-350HBW;
- (c) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.0, C not exceeding 0.5, D not exceeding 1.5; and
- (d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 2 mm flat bottom hole;
- (6) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:
- (a) Made from Electric Arc Furnace melted, Ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):
- Carbon 0.23-0.28,
 - Silicon 0.05-0.15,

- Manganese 1.20-1.50,
- Nickel not greater than 0.4,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.20-1.50,
- Molybdenum 0.35-0.55,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.5, C not exceeding 1.0, D not exceeding 1.5;

(c) Having the following mechanical properties:

(i) With a Brinell hardness not more than 237 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 75ksi min and UTS 95ksi or more, Elongation of 18% or more and Reduction of area 35% or more; having charpy V at -75 degrees F in the longitudinal direction equal or greater than 15 ft. lbs (single value) and equal or greater than 20 ft. lbs (average of 3 specimens) and conforming to the requirements of NACE MR01-75; or

(ii) With a Brinell hardness not less than 240 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 90 ksi min and UTS 110 ksi or more, Elongation of 15% or more and Reduction of area 30% or more; having charpy V at -40 degrees F in the longitudinal direction equal or greater than 21 ft. lbs (single value) and equal or greater than 31 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301;

(7) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.25-0.30,
- Silicon not greater than 0.25,
- Manganese not greater than 0.50,
- Nickel 3.0-3.5,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.0-1.5,
- Molybdenum 0.6-0.9,
- Vanadium 0.08 to 0.12
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm.

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.0(t) and 0.5(h), B not exceeding 1.5(t) and 1.0(h), C not exceeding 1.0(t) and 0.5(h), and D not exceeding 1.5(t) and 1.0(h);

(c) Having the following mechanical properties: A Brinell hardness not less than 350 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 145ksi or more and UTS 160ksi or more, Elongation of 15% or more and Reduction of area 35% or more; having charpy V at -40 degrees F in the transverse direction equal or greater than 20 ft. lbs (single value) and equal or greater than 25 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301.

The products subject to the order are currently classified in the Harmonized Tariff Schedule of the United States (HTSUS) under item numbers: 7208.40.3030, 7208.40.3060, 7208.51.0030, 7208.51.0045, 7208.51.0060, 7208.52.0000, 7211.13.0000, 7211.14.0030, 7211.14.0045, 7225.40.1110, 7225.40.1180, 7225.40.3005, 7225.40.3050, 7226.20.0000, and 7226.91.5000.

The products subject to the order may also enter under the following HTSUS item numbers: 7208.40.6060, 7208.53.0000, 7208.90.0000, 7210.70.3000, 7210.90.9000, 7211.19.1500, 7211.19.2000, 7211.19.4500, 7211.19.6000, 7211.19.7590, 7211.90.0000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7214.10.0000, 7214.30.0010, 7214.30.0080, 7214.91.0015, 7214.91.0060, 7214.91.0090, 7225.11.0000, 7225.19.0000, 7225.40.5110, 7225.40.5130, 7225.40.5160, 7225.40.7000, 7225.99.0010, 7225.99.0090, 7226.11.1000, 7226.11.9060, 7226.19.1000, 7226.19.9000, 7226.91.0500, 7226.91.1530, 7226.91.1560, 7226.91.2530, 7226.91.2560, 7226.91.7000, 7226.91.8000, and 7226.99.0180.

The HTSUS subheadings above are provided for convenience and customs purposes only. The written description of the scope of the order is dispositive.

B) Scope of the Order for CTL plate from Korea

The products covered by this order are certain carbon and alloy steel hot-rolled or forged flat plate products not in coils, whether or not painted, varnished, or coated with plastics or other non-metallic substances (cut-to-length plate). Subject merchandise includes plate that is produced by being cut-to-length from coils or from other discrete length plate and plate that is rolled or forged into a discrete length. The products covered include (1) Universal mill plates (*i.e.*, flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1250 mm, and of a thickness of not less than 4 mm, which are not in coils and without patterns in relief), and (2) hot-rolled or forged flat steel products of a thickness of 4.75 mm or more and of a width which exceeds 150 mm and measures at least twice the thickness, and which are not in coils, whether or not with patterns in relief. The covered products described above may be rectangular, square, circular or other shapes and include products of either rectangular or non-rectangular cross-section where such non-rectangular cross-section is achieved subsequent to the rolling process, *i.e.*, products which have been “worked after rolling” (*e.g.*, products which have been beveled or rounded at the edges).

For purposes of the width and thickness requirements referenced above, the following rules apply:

(1) except where otherwise stated where the nominal and actual thickness or width measurements vary, a product from a given subject country is within the scope if application of either the nominal or actual measurement would place it within the scope based on the definitions set forth above unless the product is already covered by an order existing on that specific country (*i.e.*, *Certain Hot Rolled Steel Flat Products from Australia, Brazil, Japan, the Republic of Korea, the Netherlands, the Republic of Turkey, and the United Kingdom: Amended Final Affirmative Antidumping Determinations for Australia, the Republic of Korea, and the Republic of Turkey and Antidumping Duty Orders*, 81 FR 67962 (October 3, 2016), and

(2) where the width and thickness vary for a specific product (*e.g.*, the thickness of certain products with non-rectangular cross-section, the width of certain products with non-rectangular shape, *etc.*), the measurement at its greatest width or thickness applies.

Steel products included in the scope of this order are products in which: (1) iron predominates, by weight, over each of the other contained elements; and (2) the carbon content is 2 percent or less by weight.

Subject merchandise includes cut-to-length plate that has been further processed in the subject country or a third country, including but not limited to pickling,

oiling, levelling, annealing, tempering, temper rolling, skin passing, painting, varnishing, trimming, cutting, punching, beveling, and/or slitting, or any other processing that would not otherwise remove the merchandise from the scope of the order if performed in the country of manufacture of the cut-to-length plate.

All products that meet the written physical description, are within the scope of this order unless specifically excluded or covered by the scope of an existing order. The following products are outside of, and/or specifically excluded from, the scope of this order:

- (1) products clad, plated, or coated with metal, whether or not painted, varnished or coated with plastic or other non-metallic substances;
- (2) military grade armor plate certified to one of the following specifications or to a specification that references and incorporates one of the following specifications:
 - MIL-A-12560,
 - MIL-DTL-12560H,
 - MIL-DTL-12560J,
 - MIL-DTL-12560K,
 - MIL-DTL-32332,
 - MIL-A-46100D,
 - MIL-DTL-46100-E,
 - MIL-46177C,
 - MIL-S-16216K Grade HY80,
 - MIL-S-16216K Grade HY100,
 - MIL-S-24645A HSLA-80;
 - MIL-S-24645A HSLA-100,
 - T9074-BD-GIB-010/0300 Grade HY80,
 - T9074-BD-GIB-010/0300 Grade HY100,
 - T9074-BD-GIB-010/0300 Grade HSLA80,
 - T9074-BD-GIB-010/0300 Grade HSLA100, and
 - T9074-BD-GIB-010/0300 Mod. Grade HSLA115,

except that any cut-to-length plate certified to one of the above specifications, or to a military grade armor specification that references and incorporates one of the above specifications, will not be excluded from the scope if it is also dual- or multiple-certified to any other non-armor specification that otherwise would fall within the scope of this order;

- (3) stainless steel plate, containing 10.5 percent or more of chromium by weight and not more than 1.2 percent of carbon by weight;
- (4) CTL plate meeting the requirements of ASTM A-829, Grade E 4340 that are over 305 mm in actual thickness;
- (5) Alloy forged and rolled CTL plate greater than or equal to 152.4 mm in actual thickness meeting each of the following requirements:

(a) Electric furnace melted, ladle refined & vacuum degassed and having a chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.20,
- Manganese 1.20-1.60,
- Nickel not greater than 1.0,
- Sulfur not greater than 0.007,
- Phosphorus not greater than 0.020,
- Chromium 1.0-2.5,
- Molybdenum 0.35-0.80,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) With a Brinell hardness measured in all parts of the product including mid thickness falling within one of the following ranges:

- (i) 270-300 HBW,
- (ii) 290-320 HBW, or
- (iii) 320-350HBW;

(c) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.0, C not exceeding 0.5, D not exceeding 1.5; and

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 2 mm flat bottom hole;

- (6) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, Ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.15,
- Manganese 1.20-1.50,
- Nickel not greater than 0.4,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.20-1.50,
- Molybdenum 0.35-0.55,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.5, C not exceeding 1.0, D not exceeding 1.5;

(c) Having the following mechanical properties:

(i) With a Brinell hardness not more than 237 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 75ksi min and UTS 95ksi or more, Elongation of 18% or more and Reduction of area 35% or more; having charpy V at -75 degrees F in the longitudinal direction equal or greater than 15 ft. lbs (single value) and equal or greater than 20 ft. lbs (average of 3 specimens) and conforming to the requirements of NACE MR01-75; or

(ii) With a Brinell hardness not less than 240 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 90 ksi min and UTS 110 ksi or more, Elongation of 15% or more and Reduction of area 30% or more; having charpy V at -40 degrees F in the longitudinal direction equal or greater than 21 ft. lbs (single value) and equal or greater than 31 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301;

(7) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.25-0.30,
- Silicon not greater than 0.25,
- Manganese not greater than 0.50,
- Nickel 3.0-3.5,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.0-1.5,
- Molybdenum 0.6-0.9,
- Vanadium 0.08 to 0.12
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm.

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.0(t) and 0.5(h), B not exceeding 1.5(t) and 1.0(h), C not exceeding 1.0(t) and 0.5(h), and D not exceeding 1.5(t) and 1.0(h);

(c) Having the following mechanical properties: A Brinell hardness not less than 350 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 145ksi or more and UTS 160ksi or more, Elongation of 15% or more and Reduction of area 35% or more; having charpy V at -40 degrees F in the transverse direction equal or greater than 20 ft. lbs (single value) and equal or greater than 25 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301.

At the time of the filing of the petition, there was an existing antidumping duty order on certain cut-to-length carbon-quality steel plate products from Korea. *See Notice of Final Determination of Sales at Less Than Fair Value: Certain Cut-To-Length Carbon-Quality Steel Plate Products from Korea*, 64 Fed. Reg. 73,196 (Dep't Commerce Dec. 29, 1999), as amended, 65 Fed. Reg. 6,585 (Dep't Commerce Feb 10, 2000) (1999 Korea AD Order). The scope of the antidumping duty order with regard to cut-to-length plate from Korea covers only (1) subject cut-to-length plate not within the physical description of cut-to-length carbon quality steel plate in the 1999 Korea AD Order, regardless of producer or exporter; and (2) cut-to-length plate produced and/or exported by those companies that were excluded or revoked from the 1999 Korea AD Order as of April 8, 2016. The only revoked or excluded company is Pohang Iron and Steel Company, also known as POSCO.

The products subject to the order are currently classified in the Harmonized Tariff Schedule of the United States (HTSUS) under item numbers: 7208.40.3030, 7208.40.3060, 7208.51.0030, 7208.51.0045, 7208.51.0060, 7208.52.0000, 7211.13.0000, 7211.14.0030, 7211.14.0045, 7225.40.1110, 7225.40.1180, 7225.40.3005, 7225.40.3050, 7226.20.0000, and 7226.91.5000.

The products subject to the order may also enter under the following HTSUS item numbers: 7208.40.6060, 7208.53.0000, 7208.90.0000, 7210.70.3000, 7210.90.9000, 7211.19.1500, 7211.19.2000, 7211.19.4500, 7211.19.6000, 7211.19.7590, 7211.90.0000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7214.10.0000, 7214.30.0010, 7214.30.0080, 7214.91.0015, 7214.91.0060, 7214.91.0090, 7225.11.0000, 7225.19.0000, 7225.40.5110, 7225.40.5130, 7225.40.5160, 7225.40.7000, 7225.99.0010, 7225.99.0090, 7226.11.1000, 7226.11.9060, 7226.19.1000, 7226.19.9000, 7226.91.0500, 7226.91.1530, 7226.91.1560, 7226.91.2530, 7226.91.2560, 7226.91.7000, 7226.91.8000, and 7226.99.0180.

The HTSUS subheadings above are provided for convenience and customs purposes only. The written description of the scope of the order is dispositive.

C) Scope of the Order for CTL plate from Japan

The products covered by this order are certain carbon and alloy steel hot-rolled or forged flat plate products not in coils, whether or not painted, varnished, or coated with plastics or other non-metallic substances (cut-to-length plate). Subject merchandise includes plate that is produced by being cut-to-length from coils or from other discrete length plate and plate that is rolled or forged into a discrete length. The products covered include (1) Universal mill plates (*i.e.*, flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1250 mm, and of a thickness of not less than 4 mm, which are not in coils and without patterns in relief), and (2) hot-rolled or forged flat steel products of a thickness of 4.75 mm or more and of a width which exceeds 150 mm and measures at least twice the thickness, and which are not in coils, whether or not with patterns in relief. The covered products described above may be rectangular, square, circular or other shapes and include products of either rectangular or non-rectangular cross-section where such non-rectangular cross-section is achieved subsequent to the rolling process, *i.e.*, products which have been “worked after rolling” (*e.g.*, products which have been beveled or rounded at the edges).

For purposes of the width and thickness requirements referenced above, the following rules apply:

(1) except where otherwise stated where the nominal and actual thickness or width measurements vary, a product from a given subject country is within the scope if application of either the nominal or actual measurement would place it within the scope based on the definitions set forth above unless the product is already covered by an order existing on that specific country (*i.e.*, *Certain Hot-Rolled Steel Flat Products from Australia, Brazil, Japan, the Republic of Korea, the Netherlands, the Republic of Turkey, and the United Kingdom: Amended Final Affirmative Antidumping Determinations for Australia, the Republic of Korea, and the Republic of Turkey and Antidumping Duty Orders*, 81 FR 67962 (October 3, 2016), and

(2) where the width and thickness vary for a specific product (*e.g.*, the thickness of certain products with non-rectangular cross-section, the width of certain products with non-rectangular shape, *etc.*), the measurement at its greatest width or thickness applies.

Steel products included in the scope of this order are products in which: (1) iron predominates, by weight, over each of the other contained elements; and (2) the carbon content is 2 percent or less by weight.

Subject merchandise includes cut-to-length plate that has been further processed in the subject country or a third country, including but not limited to pickling,

oiling, levelling, annealing, tempering, temper rolling, skin passing, painting, varnishing, trimming, cutting, punching, beveling, and/or slitting, or any other processing that would not otherwise remove the merchandise from the scope of the order if performed in the country of manufacture of the cut-to-length plate.

All products that meet the written physical description, are within the scope of this order unless specifically excluded or covered by the scope of an existing order. The following products are outside of, and/or specifically excluded from, the scope of this order:

- (1) products clad, plated, or coated with metal, whether or not painted, varnished or coated with plastic or other non-metallic substances;
- (2) military grade armor plate certified to one of the following specifications or to a specification that references and incorporates one of the following specifications:
 - MIL-A-12560,
 - MIL-DTL-12560H,
 - MIL-DTL-12560J,
 - MIL-DTL-12560K,
 - MIL-DTL-32332,
 - MIL-A-46100D,
 - MIL-DTL-46100-E,
 - MIL-46177C,
 - MIL-S-16216K Grade HY80,
 - MIL-S-16216K Grade HY100,
 - MIL-S-24645A HSLA-80;
 - MIL-S-24645A HSLA-100,
 - T9074-BD-GIB-010/0300 Grade HY80,
 - T9074-BD-GIB-010/0300 Grade HY100,
 - T9074-BD-GIB-010/0300 Grade HSLA80,
 - T9074-BD-GIB-010/0300 Grade HSLA100, and
 - T9074-BD-GIB-010/0300 Mod. Grade HSLA115,

except that any cut-to-length plate certified to one of the above specifications, or to a military grade armor specification that references and incorporates one of the above specifications, will not be excluded from the scope if it is also dual- or multiple-certified to any other non-armor specification that otherwise would fall within the scope of this order;

- (3) stainless steel plate, containing 10.5 percent or more of chromium by weight and not more than 1.2 percent of carbon by weight;
- (4) CTL plate meeting the requirements of ASTM A-829, Grade E 4340 that are over 305 mm in actual thickness;
- (5) Alloy forged and rolled CTL plate greater than or equal to 152.4 mm in actual thickness meeting each of the following requirements:

(a) Electric furnace melted, ladle refined & vacuum degassed and having a chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.20,
- Manganese 1.20-1.60,
- Nickel not greater than 1.0,
- Sulfur not greater than 0.007,
- Phosphorus not greater than 0.020,
- Chromium 1.0-2.5,
- Molybdenum 0.35-0.80,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) With a Brinell hardness measured in all parts of the product including mid thickness falling within one of the following ranges:

- (i) 270-300 HBW,
- (ii) 290-320 HBW, or
- (iii) 320-350HBW;

(c) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.0, C not exceeding 0.5, D not exceeding 1.5; and

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 2 mm flat bottom hole;

- (6) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, Ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.15,
- Manganese 1.20-1.50,
- Nickel not greater than 0.4,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.20-1.50,
- Molybdenum 0.35-0.55,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.5, C not exceeding 1.0, D not exceeding 1.5;

(c) Having the following mechanical properties:

(i) With a Brinell hardness not more than 237 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 75ksi min and UTS 95ksi or more, Elongation of 18% or more and Reduction of area 35% or more; having charpy V at -75 degrees F in the longitudinal direction equal or greater than 15 ft. lbs (single value) and equal or greater than 20 ft. lbs (average of 3 specimens) and conforming to the requirements of NACE MR01-75; or

(ii) With a Brinell hardness not less than 240 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 90 ksi min and UTS 110 ksi or more, Elongation of 15% or more and Reduction of area 30% or more; having charpy V at -40 degrees F in the longitudinal direction equal or greater than 21 ft. lbs (single value) and equal or greater than 31 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301;

(7) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:

(a) Made from Electric Arc Furnace melted, ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.25-0.30,
- Silicon not greater than 0.25,
- Manganese not greater than 0.50,
- Nickel 3.0-3.5,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.0-1.5,
- Molybdenum 0.6-0.9,
- Vanadium 0.08 to 0.12
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm.

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.0(t) and 0.5(h), B not exceeding 1.5(t) and 1.0(h), C not exceeding 1.0(t) and 0.5(h), and D not exceeding 1.5(t) and 1.0(h);

(c) Having the following mechanical properties: A Brinell hardness not less than 350 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 145ksi or more and UTS 160ksi or more, Elongation of 15% or more and Reduction of area 35% or more; having charpy V at -40 degrees F in the transverse direction equal or greater than 20 ft. lbs (single value) and equal or greater than 25 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301.

The products subject to the order are currently classified in the Harmonized Tariff Schedule of the United States (HTSUS) under item numbers: 7208.40.3030, 7208.40.3060, 7208.51.0030, 7208.51.0045, 7208.51.0060, 7208.52.0000, 7211.13.0000, 7211.14.0030, 7211.14.0045, 7225.40.1110, 7225.40.1180, 7225.40.3005, 7225.40.3050, 7226.20.0000, and 7226.91.5000.

The products subject to the order may also enter under the following HTSUS item numbers: 7208.40.6060, 7208.53.0000, 7208.90.0000, 7210.70.3000, 7210.90.9000, 7211.19.1500, 7211.19.2000, 7211.19.4500, 7211.19.6000, 7211.19.7590, 7211.90.0000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7214.10.0000, 7214.30.0010, 7214.30.0080, 7214.91.0015, 7214.91.0060, 7214.91.0090, 7225.11.0000, 7225.19.0000, 7225.40.5110, 7225.40.5130, 7225.40.5160, 7225.40.7000, 7225.99.0010, 7225.99.0090, 7226.11.1000, 7226.11.9060, 7226.19.1000, 7226.19.9000, 7226.91.0500, 7226.91.1530, 7226.91.1560, 7226.91.2530, 7226.91.2560, 7226.91.7000, 7226.91.8000, and 7226.99.0180.

The HTSUS subheadings above are provided for convenience and customs purposes only. The written description of the scope of the order is dispositive.

D) Scope of the Order for CTL plate from Taiwan

The products covered by this order are certain carbon and alloy steel hot-rolled or forged flat plate products not in coils, whether or not painted, varnished, or coated with plastics or other non-metallic substances (cut-to-length plate). Subject merchandise includes plate that is produced by being cut-to-length from coils or from other discrete length plate and plate that is rolled or forged into a discrete length. The products covered include (1) Universal mill plates (*i.e.*, flat-rolled products rolled on four faces or in a closed box pass, of a width exceeding 150 mm but not exceeding 1250 mm, and of a thickness of not less than 4 mm, which are not in coils and without patterns in relief), and (2) hot-rolled or forged flat steel products of a thickness of 4.75 mm or more and of a width which exceeds 150 mm and measures at least twice the thickness, and which are not in coils, whether or not with patterns in relief. The covered products described above may be rectangular, square, circular or other shapes and include products of either rectangular or non-rectangular cross-section where such non-rectangular cross-section is achieved subsequent to the rolling process, *i.e.*, products which have been “worked after rolling” (*e.g.*, products which have been beveled or rounded at the edges).

For purposes of the width and thickness requirements referenced above, the following rules apply:

(1) except where otherwise stated where the nominal and actual thickness or width measurements vary, a product from a given subject country is within the scope if application of either the nominal or actual measurement would place it within the scope based on the definitions set forth above unless the product is already covered by an order existing on that specific country (*i.e. Notice of Antidumping Duty Order; Certain Hot-Rolled Carbon Steel Flat Products From Taiwan*, 66 FR 59563 (November 29, 2001)); and

(2) where the width and thickness vary for a specific product (*e.g.*, the thickness of certain products with non-rectangular cross-section, the width of certain products with non-rectangular shape, *etc.*), the measurement at its greatest width or thickness applies.

Steel products included in the scope of this order are products in which: (1) iron predominates, by weight, over each of the other contained elements; and (2) the carbon content is 2 percent or less by weight.

Subject merchandise includes cut-to-length plate that has been further processed in the subject country or a third country, including but not limited to pickling, oiling, levelling, annealing, tempering, temper rolling, skin passing, painting, varnishing, trimming, cutting, punching, beveling, and/or slitting, or any other

processing that would not otherwise remove the merchandise from the scope of the order if performed in the country of manufacture of the cut-to-length plate.

All products that meet the written physical description, are within the scope of this order unless specifically excluded or covered by the scope of an existing order. The following products are outside of, and/or specifically excluded from, the scope of this order:

- (1) products clad, plated, or coated with metal, whether or not painted, varnished or coated with plastic or other non-metallic substances;
- (2) military grade armor plate certified to one of the following specifications or to a specification that references and incorporates one of the following specifications:
 - MIL-A-12560,
 - MIL-DTL-12560H,
 - MIL-DTL-12560J,
 - MIL-DTL-12560K,
 - MIL-DTL-32332,
 - MIL-A-46100D,
 - MIL-DTL-46100-E,
 - MIL-46177C,
 - MIL-S-16216K Grade HY80,
 - MIL-S-16216K Grade HY100,
 - MIL-S-24645A HSLA-80;
 - MIL-S-24645A HSLA-100,
 - T9074-BD-GIB-010/0300 Grade HY80,
 - T9074-BD-GIB-010/0300 Grade HY100,
 - T9074-BD-GIB-010/0300 Grade HSLA80,
 - T9074-BD-GIB-010/0300 Grade HSLA100, and
 - T9074-BD-GIB-010/0300 Mod. Grade HSLA115,

except that any cut-to-length plate certified to one of the above specifications, or to a military grade armor specification that references and incorporates one of the above specifications, will not be excluded from the scope if it is also dual- or multiple-certified to any other non-armor specification that otherwise would fall within the scope of this order;

- (3) stainless steel plate, containing 10.5 percent or more of chromium by weight and not more than 1.2 percent of carbon by weight;

- (4) CTL plate meeting the requirements of ASTM A-829, Grade E 4340 that are over 305 mm in actual thickness;
- (5) Alloy forged and rolled CTL plate greater than or equal to 152.4 mm in actual thickness meeting each of the following requirements:
- (a) Electric furnace melted, ladle refined & vacuum degassed and having a chemical composition (expressed in weight percentages):
- Carbon 0.23-0.28,
 - Silicon 0.05-0.20,
 - Manganese 1.20-1.60,
 - Nickel not greater than 1.0,
 - Sulfur not greater than 0.007,
 - Phosphorus not greater than 0.020,
 - Chromium 1.0-2.5,
 - Molybdenum 0.35-0.80,
 - Boron 0.002-0.004,
 - Oxygen not greater than 20 ppm,
 - Hydrogen not greater than 2 ppm, and
 - Nitrogen not greater than 60 ppm;
- (b) With a Brinell hardness measured in all parts of the product including mid thickness falling within one of the following ranges:
- (i) 270-300 HBW,
 - (ii) 290-320 HBW, or
 - (iii) 320-350HBW;
- (c) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.0, C not exceeding 0.5, D not exceeding 1.5; and
- (d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 2 mm flat bottom hole;
- (6) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:
- (a) Made from Electric Arc Furnace melted, Ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):

- Carbon 0.23-0.28,
- Silicon 0.05-0.15,
- Manganese 1.20-1.50,
- Nickel not greater than 0.4,
- Sulfur not greater than 0.010,
- Phosphorus not greater than 0.020,
- Chromium 1.20-1.50,
- Molybdenum 0.35-0.55,
- Boron 0.002-0.004,
- Oxygen not greater than 20 ppm,
- Hydrogen not greater than 2 ppm, and
- Nitrogen not greater than 60 ppm;

(b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.5, B not exceeding 1.5, C not exceeding 1.0, D not exceeding 1.5;

(c) Having the following mechanical properties:

(i) With a Brinell hardness not more than 237 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 75ksi min and UTS 95ksi or more, Elongation of 18% or more and Reduction of area 35% or more; having charpy V at -75 degrees F in the longitudinal direction equal or greater than 15 ft. lbs (single value) and equal or greater than 20 ft. lbs (average of 3 specimens) and conforming to the requirements of NACE MR01-75; or

(ii) With a Brinell hardness not less than 240 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 90 ksi min and UTS 110 ksi or more, Elongation of 15% or more and Reduction of area 30% or more; having charpy V at -40 degrees F in the longitudinal direction equal or greater than 21 ft. lbs (single value) and equal or greater than 31 ft. lbs (average of 3 specimens);

(d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and

(e) Conforming to magnetic particle inspection in accordance with AMS 2301;

- (7) Alloy forged and rolled steel CTL plate over 407 mm in actual thickness and meeting the following requirements:
- (a) Made from Electric Arc Furnace melted, ladle refined & vacuum degassed, alloy steel with the following chemical composition (expressed in weight percentages):
- Carbon 0.25-0.30,
 - Silicon not greater than 0.25,
 - Manganese not greater than 0.50,
 - Nickel 3.0-3.5,
 - Sulfur not greater than 0.010,
 - Phosphorus not greater than 0.020,
 - Chromium 1.0-1.5,
 - Molybdenum 0.6-0.9,
 - Vanadium 0.08 to 0.12
 - Boron 0.002-0.004,
 - Oxygen not greater than 20 ppm,
 - Hydrogen not greater than 2 ppm, and
 - Nitrogen not greater than 60 ppm.
- (b) Having cleanliness in accordance with ASTM E45 method A (Thin and Heavy): A not exceeding 1.0(t) and 0.5(h), B not exceeding 1.5(t) and 1.0(h), C not exceeding 1.0(t) and 0.5(h), and D not exceeding 1.5(t) and 1.0(h);
- (c) Having the following mechanical properties: A Brinell hardness not less than 350 HBW measured in all parts of the product including mid thickness; and having a Yield Strength of 145ksi or more and UTS 160ksi or more, Elongation of 15% or more and Reduction of area 35% or more; having charpy V at -40 degrees F in the transverse direction equal or greater than 20 ft. lbs (single value) and equal or greater than 25 ft. lbs (average of 3 specimens);
- (d) Conforming to ASTM A578-S9 ultrasonic testing requirements with acceptance criteria 3.2 mm flat bottom hole; and
- (e) Conforming to magnetic particle inspection in accordance with AMS 2301.

The products subject to the order are currently classified in the Harmonized Tariff Schedule of the United States (HTSUS) under item numbers: 7208.40.3030,

7208.40.3060, 7208.51.0030, 7208.51.0045, 7208.51.0060, 7208.52.0000, 7211.13.0000, 7211.14.0030, 7211.14.0045, 7225.40.1110, 7225.40.1180, 7225.40.3005, 7225.40.3050, 7226.20.0000, and 7226.91.5000.

The products subject to the order may also enter under the following HTSUS item numbers: 7208.40.6060, 7208.53.0000, 7208.90.0000, 7210.70.3000, 7210.90.9000, 7211.19.1500, 7211.19.2000, 7211.19.4500, 7211.19.6000, 7211.19.7590, 7211.90.0000, 7212.40.1000, 7212.40.5000, 7212.50.0000, 7214.10.0000, 7214.30.0010, 7214.30.0080, 7214.91.0015, 7214.91.0060, 7214.91.0090, 7225.11.0000, 7225.19.0000, 7225.40.5110, 7225.40.5130, 7225.40.5160, 7225.40.7000, 7225.99.0010, 7225.99.0090, 7226.11.1000, 7226.11.9060, 7226.19.1000, 7226.19.9000, 7226.91.0500, 7226.91.1530, 7226.91.1560, 7226.91.2530, 7226.91.2560, 7226.91.7000, 7226.91.8000, and 7226.99.0180.

The HTSUS subheadings above are provided for convenience and customs purposes only. The written description of the scope of the order is dispositive.
[FR Doc. 2017-10757 Filed: 5/24/2017 8:45 am; Publication Date: 5/25/2017]